# **Home Automation System Using Internet of Things**

K.Ramya<sup>1</sup>, G.Arunachalam<sup>2</sup>, R.Karthika<sup>3</sup>, K.Kiruthiga<sup>4</sup>

Department of MCA,ECE

<sup>1,2</sup> Assistant Professor, Gnanamani College Of Technology& Engineering, Pachal, Namakkal, Tamilnadu, India <sup>3,4</sup> Student, Gnanamani College Of Technology& Engineering, Pachal, Namakkal, Tamilnadu, India

Abstract- With advancement of Automation technology, life is getting simpler and easier in all aspects. In today's world Automatic systems are being preferred over manual system. With the rapid increase in the number of users of internet over the past decade has made Internet a part and parcel of life, and IoT is the latest and emerging internet technology. Internet of things is a growing network of everyday objectfrom industrial machine to consumer goods that can share information and complete tasks while you are busy with other activities. Wireless Home Automation system(WHAS) using IoT is a system that uses computers or mobile devices to control basic home functions and features automatically through internet from anywhere around the world, an automated home is sometimes called a smart home. It is meant to save the electric power and human energy. The home automation system differs from other system by allowing the user to operate the system from anywhere around the world through internet connection.

In this journal we present a Home Automation system(HAS) using Intel Galileo that employs the integration of cloud networking, wireless communication, to provide the user with remote control of various lights, fans, and appliances within their home and storing the data in the cloud. The system will automatically change on the basis of sensors' data. This system is designed to be low cost and expandable allowing a variety of devices to be controlled.

*Keywords*- Home automation System (HAS), Internet of Things (IoT), Cloud networking, Wi-Fi network, Intel Galileo Microcontroller.

# I. INTRODUCTION

A. Overview: Homes of the 21st century will become more and more self- controlled and automated due to the comfort it provides, especially when employed in a private home. A home automation system is a means that allow users to control electric appliances of varying kind. Many existing, wellestablished home automation systems are based on wired communication. This does not pose a problem until the system is planned well in advance and installed during the physical construction of the building. But for already existing buildings the implementation cost goes very high. In contrast, Wireless systems can be of great help for automation systems. With the advancement of wireless technologies such as Wi-Fi, cloud networks in the recent past, wireless systems are used every day and everywhere.

B. Advantages of Home automation systems:

In recent years, wireless systems like Wi-Fi have become more and more common in home networking. Also in Home &Building automation systems, the use of wireless technologies gives several advantages that could not be achieved using a wired network only.

1) Reduced installation costs: First and foremost, installation costs are significantly reduced since no cabling is necessary. Wired solutions require cabling, where material as well as the professional laying of cables (e.g. into walls) is expensive.

2) System scalability and easy extension: Deploying a wireless network is especially advantageous when, due to new or changed requirements, extension of the network is necessary. In contrast to wired installations, in which cabling extension is tedious. This makes wireless installations a seminal investment.

3) Aesthetical benefits: Apart from covering a larger area, this attribute helps to full aesthetical requirements as well. Examples include representative buildings with all-glass architecture and historical buildings where design or conservatory reasons do not allow laying of cables.

4) Integration of mobile devices: With wireless networks, associating mobile devices such as PDAs and Smartphones with the automation system becomes possible everywhere and at any time, as a device's exact physical location is no longer crucial for a connection (as long as the device is in reach of the network).

For all these reasons, wireless technology is not only an attractive choice in renovation and refurbishment, but also for new installations.

# **II. SYSTEM ANALYSIS**

# A. Problem Definition

Home automation systems face four main challenges, these are high cost of ownership, inflexibility, poor

manageability, and difficulty in achieving security. The main objectives of this research is to design and implement a home automation system using IoT that is capable of controlling and automating most of the house appliances through an easy manageable web interface. The proposed system has a great flexibility by using Wi-Fi technology to interconnect its distributed sensors to home automation server. This will decrease the deployment cost and will increase the ability of upgrading, and system reconfiguration.

## B. Proposed System Feature

The proposed system is a distributed home automation system, consists of server, sensors. Server controls and monitors the various sensors, and can be easily configured to handle more hardware interface module (sensors). The Intel Galileo development board, with built in WiFi card port to which the card is inserted, acts as web server. Automation System can be accessed from the web browser of any local PC in the same LAN using server IP, or remotely from any PC or mobile handheld device connected to the internet with appropriate web browser through server real IP (internet IP). WiFi technology is selected to be the network infrastructure that connects server and the sensors. WiFi is chosen to improve system security (by using secure WiFi connection), and to increase system mobility and scalability

## **III. SYSTEM DESIGN & IMPLEMENTATION**

Proposed Home Automation System:.



Proposed Model of Home Automation System

The proposed model of the home automation system is as shown in the figure1. The model consist of different sensors like temperature, gas, motion and LDR. Initially the Intel Galileo connects to the internet through WiFi. When the connection is established it will start reading the parameters of sensors like p1, p2, p3 etc. The threshold levels for the required sensors are set as t1, t2, t3 etc. The sensor data are sent to the web server and stored in the cloud. The data can be analyzed anywhere any time. If the sensor parameters are greater than the threshold level then the respective alarm a1, a2, a3 etc. will be raised and the required actuation is done for the controlling of the parameters. In the proposed model the temperature, gas leakage, motion in the house is monitored. The temperature and the motion detection is stored in cloud for analysis. If the temperature exceeds the threshold level then the cooler will turn on automatically and it will off when the temperature comes to control. Similarly when there is a leakage of gas in the house alarm is raised giving the alert sound. The required lights are turned on/off automatically by detecting the light outside the house. The user can also monitor the electric appliances through the internet via web server. If the lights or any electrical appliances are left on in hurry can be seen and turned off remotely through simply typing the IP address of the web server.

## B. Proposed Home Automation System

# Functions

The proposed home automation system has the capabilities to control the following components in users home and monitor the following alarms:

- Temperature and humidity
- Motion detection
- Fire and smoke detection
- Light level
- The proposed home automation system can control the following appliance:
- Lights on/off/dim
- Fan on/off
- On/off different appliance.

# C. Software design

# Front End Design:

HTML is a format that tells a computer how to display a web page. The documents themselves are plain text files with special "tags" or codes that a web browser uses to interpret and display information on your computer screen. HTML stands for Hyper Text Markup Language; an HTML file is a text file containing small markup tags. The markup tags tell the Web browser how to display the page. An HTML files must have an htm or html file extension. Cloud Storage:

Cloud computing is the practice of using remote servers on the internet to manage, store and process data instead of using a personal computer.

Cloud computing is a general term that is better divided into three categories: Infrastructure-as-a- Service, Platform-as-a-Service, and Software-as-a- Service. IaaS (or utility computing) follows a traditional utilities model, providing servers and storage on demand with the consumer paying accordingly. PaaS allows for the construction of applications within a provider's framework, like Google's App Engine. SaaS enables customers to use an application on demand via a browser. A common example of cloud computing is Gmail, where you can access your stored data from any computer with internet access. Here we are using Gmail for the storage of the data. This journal proposes a new design for the smart home using the wireless sensor network and the biometric technologies.

#### D. Implementation Setup :



Sequence of Activities in WHAS

Above Figure illustrates the sequence of activities in the WHAS. When the connection is established it will start reading the parameters of sensors like p1, p2, p3 etc. The threshold levels for the required sensors are set as t1, t2, t3 etc. The sensor data are sent to the web server and stored in the cloud. The data can be analyzed anywhere any time. If the sensor parameters are greater than the threshold level then the respective alarm a1, a2, a3 etc. will be raised and the required actuation is done for the controlling of the parameters.



Experimental setup of HAS

A model house is built for the home automation system and is as shown in the Above Figure.

At the door of the house a motion sensor is fixed to detect any movement near the door. Light 1 will turn on automatically when light sensor detects the darkness. A cooler/Fan will turn on when the room temperature exceeds the set threshold and in turn reduces the room temperature. The gas sensor MQ-6 is placed in the kitchen to detect any gas leakage, if any leakage is detected the alarm in the hall is raised. Relay is used to switch the electrical appliances like light, fan etc. The Intel Galileo is placed in store room or garage. The Intel Galileo is connected with WiFi card with the antennas for the connectivity with internet.

# **IV. RESULTS**



After the successful connection to the server, the data of sensor are sent to the web server for monitoring of the system. The figure 4 shows the web server page which will allow us to monitor and control the system. By entering the assigned IP address in the web browser this web server page will appear. The web server gives the information about the temperature in different places of the house and motion state in the house. It also gives the status of the various electrical appliances like light, fan etc which we can control remotely.

All the required data is stored in the cloud (Gmail). The stored data can be analyzed at anytime and anywhere. The figure 5 shows the temperature in degree Celsius stored at different time intervals. And also it shows the state of the motion detector along with the time. It also provides information about time of motion detected and how many times as well. All this information is stored in the cloud which can be checked by the user any time when away from home.

*	C7 #	//doos-grougle.co	•••• "	1-67121-9914
111 A	popul de Honnaberster BLB	Participation	and been been seen and the	çettron 👔 🥔 yîşelî
80	Plane Automation Date	a (Managerraning) - Mar server Dana Tools, mar-	77 7. 77	
201				-
1.1	-	And in Concession, Name	Treasure there find	
	0.002/010110/24 40	99 (1974)	THE PARTY.	
	01000-0010-17-186-04C	100.0197.A2	int Appendi	
	CONTRACTOR OF A REAL ADDRESS	304.0100.4.P	and hundred.	
	and an and the second s	and the second second	The Assessed	
	0100-00440-17.147.00	21.000042	00 (0APR)	
	-10100-00110-17-547-00V	0.010142	and states -	
	10000000000000000000000000000000000000	101.0101.00	100 (100 lb or 10 lb or 10	
-	\$436-0816-17107-54	98.23642	107 Advance-Trainer in	-
	0100-0010 17.007.00	94.2004	100 . Scherter,	
198	enciencement AD AD that	NL010140	. Int., Ayanta.	
- 14	COMMONTER TO ANY DES	84.0.0040	cont instantia	
1400	Included and a strategy and		Intel Survey	
- 14	01002-010100 111 clar 444	This contents P	in televisi	
-	inclusion with a Yalls with	and a second second	int hadden	
- 10	in an even the second second	and a state of the	. Incl Including	
- 14	invite instances a property and	00.010.45	the behaver	
1411	Comparison and A Property and	00.00142	and heaters	
	contractioner and a fit state that	And conversion.	cont Automation	
100	and an and the second s	and confidence	test factories	
44	Decision and a lot to be a lot	And Transfer	conv instantoni	
100	DOMESTIC: NOTION AND	ALC DIMENT	The states	
1.20	and include and the first state	and cookers?	and the second	
20	CONTRACTOR OF A PARTY NAME.	the submer	day industry	
1.00	The second second second second	and the second second	and installed	

Database of the sensors data stored in the cloud

All the required data is stored in the cloud (Gmail). The stored data can be analyzed at anytime and anywhere. The figure 5 shows the temperature in degree Celsius stored at different time intervals. And also it shows the state of the motion detector along with the time. It also provides information about time of motion detected and how many times as well. All this information is stored in the cloud which can be checked by the user any time when away from home.



The graph shown in the above figure gives the analysis of the temperature at different time and threshold level of the temperature. By seeing the graph we can come to know the change in the temperature. And at what time the temperature was low/ high. We can also know that was temperature was above the threshold level or not, if was above then at what time.

## V. CONCLUSION

The home automation using Internet of Things has been experimentally proven to work satisfactorily by connecting simple appliances to it and the appliances were successfully controlled remotely through internet. The designed system not only monitors the sensor data, like temperature, gas, light, motion sensors, but also actuates a process according to the requirement, for example switching on the light when it gets dark. It also stores the sensor parameters in the cloud (Gmail) in a timely manner. This will help the user to analyze the condition of various parameters in the home anytime anywhere.

# **FUTURE WORK**

Using this system as framework, the system can be expanded to include various other options which could include home security feature like capturing the photo of a person moving around the house and storing it onto the cloud. This will reduce the data storage than using the CCTV camera which will record all the time and stores it. The system can be expanded for energy monitoring, or weather stations. This kind of a system with respective changes can be implemented in the hospitals for disable people or in industries where human invasion is impossible or dangerous, and it can also be implemented for environmental monitoring.

## REFERENCES

- Sirsath N. S, Dhole P. S, Mohire N. P, Naik S. C & Ratnaparkhi N.S Department of Computer Engineering, 44, Vidyanagari, Parvati, Pune-411009, India University of Pune, "Home Automation using Cloud Network and Mobile Devices".
- [2] Deepali Javale, Mohd. Mohsin, Shreerang Nandanwar "Home Automation and Security System Using Android ADK" in International Journal of Electronics Communication and Computer Technology (IJECCT) Volume 3 Issue 2 (March 2013).
- [3] Charith Perera, Student Member, IEEE, Arkady Zaslavsky, Member, IEEE, Peter Christen, and Dimitrios Georgakopoulos, Member, IEEE "Context Aware Computing for The Internet of Things: A Survey". IEEE COMMUNICATIONS SURVEYS & TUTORIAL.
- [4] K.Ramya and K.Pavithradevi "Effective Wireless Communication," International Journal of Advanced Research, volume4(12),pp. 1559-1562 Dec 2016.
- [5] G.Arunachalam, K.Ramya, M.Vimala,
  M.Shanmugapriya, C.Krishnaveni,"Future Principle of TCP High-Speed Network "International Journal for Research & Development in Technology.

- [6] Charith Perera\_y, Arkady Zaslavskyy, Peter Christen\_ and Dimitrios Georgakopoulosy Research School of Computer Science, The Australian National University, Canberra, ACT 0200, Australia yCSIRO ICT Center, Canberra, ACT 2601, Australia "CA4IOT: Context Awareness for Internet of Things".
- [7] Bill N. Schilit, Norman Adams, and Roy Want, "Context-Aware Computing Applications".
- [8] Jayavardhana Gubbi, ,Rajkumar Buyya, Slaven Marusic,a Marimuthu Palaniswamia, "Internet of Things (IoT): A Vision, Architectural Elements, and Future Directions".
- [9] S.P. Pande, Prof. Pravin Sen, "Review On: Home Automation System For Disabled People Using BCI" in IOSR Journal of Computer Science (IOSR-JCE) e- ISSN: 2278-0661, p-ISSN: 2278-8727 PP 76-80.
- [10] Basil Hamed, "Design & Implementation of Smart House Control Using LabVIEW" at International Journal of Soft Computing and Engineering (IJSCE) ISSN: 2231-2307, Volume-1, Issue-6, January 2012.
- [11] Basma M. Mohammad El-Basioni1, Sherine M. Abd Elkader2 and Mahmoud Abdelmonim Fakhreldin3, "Smart Home Design using Wireless Sensor Network and Biometric Technologies" at Volume 2, Issue 3, March 2013.
- [12] Inderpreet Kaur, "Microcontroller Based Home Automation System With Security" at IJACSA) International Journal of Advanced Computer Science and