

Visibility Restoration of Hazy Images Using HSI Color Space

S Anjana¹, Prof. N Jeenath Laila²

^{1,2} Dept of Computer Science and Engineering

^{1,2} Government College of Engineering, Tirunelveli

Abstract- We develop a novel and effective de-hazing algorithm in HSI (Hue, Saturation and Intensity) color space in order to improve the visibility of a single hazy image. First the input hazy image is converted to HSI color space; then a gamma-correction technique is built for saturation component image processing. In addition, we implement the adaptive histogram equalization method in the intensity channel processing. Compared with the earlier haze removal methods, the experimental results demonstrate that the developed method can achieve better visual effect and better color restoration. Both qualitative evaluations and quantitative assessments indicate that the proposed method achieves a better performance than the state-of-the-art methods.

Keywords- HSI Color space, Gamma-Correction, Adaptive Histogram Equalization

I. INTRODUCTION

The rapid development of computer technology and remote-sensing techniques has brought new opportunities for the application of remote-sensing image processing. The images are widely used in basic geographic information acquisition, agricultural production, marine monitoring and other fields because of their wide coverage and high resolution [1–3]. Nearly all images acquired by passive optical remote sensing are disturbed by clouds, fog, haze and other weather factors, resulting in light being absorbed and scattered by turbid media such as particles and water droplets in the atmosphere [4–6]. The removal of haze from a single remote-sensing image is still a significant task.

At present, dehazing methods can be divided into two main categories. The first is methods based on image enhancement; the second is based on physical models. Methods in first category enhance degraded images and improve quality, and existing mature image processing algorithms can be applied to haze removal. However, the method in this category may result in some information in the images being lost. The histogram equalization method, which is based on the gray-level cumulative distribution function of the image, can also be used for dehazing. The essence of histogram equalization is the non-linear stretching of an image

to enhance contrast [7– 9]. In foggy weather, the low-frequency component of the image is enhanced, so a high-pass filter can be used to filter the image to suppress the low-frequency and enhance the high-frequency. At present, holomorphic filtering is being widely studied to remove haze [10]. According to Retinex theory, if we can find a way to separate the re- flected component from the image, then the effect of the incident component on the image is reduced to enhance the image. In the development of Retinex theory, the path-based Retinex algorithm and the iterative Retinex algorithm have appeared successively. These algorithms are highly complex, and adjusting their parameters are difficult [11,12].

The second category includes the atmospheric scattering model based on the research of the atmospheric suspended-particles scattering effect on light. This is a special method for image restoration and has a good effect on complex-scene image processing. Therefore, the information in the image can be preserved completely and haze can be removed. Tan [13] first proposed a single image dehazing method by maximizing the local contrast of the image. However, Tan’s proposed method can easily cause color over saturation when processing dense haze images. He *et al.* [14] summarized a rule, called the dark channel prior (DCP) based on observing the statistical characteristics pertaining to a large number of haze-free images. Among the above de-hazing methods, He’s method is simple and effective. However, the DCP methods are based on the statistics of outdoor images while remote-sensing images have an imaging distance different from outdoor images. As a result, color drift can easily occur when that method is applied to remote- sensing images.

In this paper, we propose a novel haze-removal method for a single image. In order maintain the color information of the original image and to remove haze better, we transform the hazy image into HSI color space; then, we build a gamma-correction technique for the for saturation component image processing. In addition,

we implement the adaptive histogram equalization method in the intensity channel processing. Compared with

the earlier methods for removing haze from hazy images, the proposed method achieves better visual effect in color restoration and haze removal.

II. METHODOLOGY

1. The physical hazy image degradation model

Nayer *et al.* [15, 16] described and deduced in detail the atmospheric scattering model, which was widely referred to by later researchers. In that model, the effect of atmosphere on the light reflected from scenery is divided into two parts: the attenuation by the atmosphere of light the scenery and the superposition of environment light. Attenuation refers to light reflected by the scene reaching to the observer after having been scattered by atmospheric particles. The image degradation model is expressed in RGB space as follows:

$$\mathbf{I}(x) = \mathbf{J}(x)t(x) + \mathbf{A}(1 - t(x)), \quad (1)$$

where x represents the position of the pixel in the image, $\mathbf{I}(x)$ is the intensity of the observed hazy image, $\mathbf{J}(x)$ is the scene radiance, \mathbf{A} is the global atmospheric light which is usually assumed to be constant, and $t(x)$ is the medium transmission, which describes the fraction of the light that is not scattered and gets to the camera.

2. Color space conversion

The main purpose of the RGB color space is for the representation and display of images in electronic systems, such as televisions and computers. The color information collected from the pixels by common devices is stored by dividing it into R (red), G (green) and B (blue). However, in RGB color model, the chrominance information is vulnerable to brightness [16].

The existence of haze submerges the object's light in the intensity channel, which could lead to a low contrast image. What's more, the saturation component is slightly affected due




Fig 1: (a) input image, from the input image obtained (b) hue image, (c) saturation image, (d) intensity image

The different scattering co-efficients, which will be discussed in next section. When people observe objects, they tend to describe them in terms of hue, saturation and brightness (HSI). HSI color space is widely used in computer vision processing algorithms, and the HSI model is more suitable for the subjective description and interpretation of the human eyes. The image is divided into a color component and a gray component, which will make the application of our image processing method more convenient in HSI color space [17,18]. The conversion from RGB color space to HSI color space can be achieved by using the following formulas. The hue component is calculated as,

$$H = \begin{cases} \theta, & B \leq G \\ 360 - \theta, & B > G \end{cases} \quad (2)$$

Where,

$$\theta = \arccos\left\{\frac{1/2[(R-G)+(R-B)]}{((R-G)^2+(R-B)(G-B))^{1/2}}\right\} \quad (3)$$

The saturation component is given as:

$$S = 1 - \frac{3}{R+G+B} [\min(R, G, B)], \quad (4)$$

Finally, the intensity component is given by:

$$I = \frac{1}{3} (R + G + B) \quad (5)$$

3. Dehazing method

By comparing and analyzing the image dehazing experimental results for the H , S , and I components, we found that the saturation component and the brightness component were positively correlated with the concentration of haze, and that the H component undergoes no obvious change before and after haze removal processing. And the results are shown in Fig. 1. Therefore, a hazy image is transformed from RGB color space into HSI color space for image processing, and the intensity and the saturation




FIG 2: Overall flowchart of proposed system

components are changed while the hue component remains unchanged. The overall flowchart of the proposed method is shown in Fig. 2.

For a haze-free image, the saturation value of each pixel is relatively large. Because of the existence of fog, the saturation of atmospheric light is introduced, resulting in the dilution of saturation. Thus, we established a gamma correction technique to estimate the saturation $S(x, y)$ component:

$$S(x, y) = \theta_0 + \theta_1 S_1(x, y) + \theta_2 S_A(x, y) \quad (6)$$

where $\theta_i, i \in (0, 1, 2)$, represents non negative coefficients, $S_1(x, y)$ is the saturation of a hazy image, and $S_A(x, y)$ represents the saturation of atmospheric light. The gradient descent method is applied to learn θ_i , and a cost function $J(\theta_i)$ is introduced, which is the sum of squares of all modeling error, $J(\theta_i)$ can be described using:

$$J(\theta) = \frac{1}{2m} \sum_{i=1}^m (s_{\theta}(X^i) - Y^i)^2 \quad (7)$$

where m is the total number of training samples and y_i is the actual value of the samples. We can obtain the coefficients by minimizing the cost function. At first, we randomly select a combination of parameters $(\theta_0, \theta_1, \theta_2)$ to calculate the cost function; then, we look for the next combination of parameters to make the value drop most until

the cost function reaches a local minimum. The derivative of the cost function is calculated as

$$\frac{\partial}{\partial \theta_j} J(\theta) = \frac{\partial}{\partial \theta_j} - \frac{1}{2m} \sum_{i=1}^m (s_{\theta}(X^i) - Y^i)^2 \quad (8)$$

According to the gradient descent algorithm we have

$$\theta_j := \theta_j - \alpha \frac{\partial}{\partial \theta_j} J(\theta) \quad (9)$$

θ is updated during descent, hence we have the following expressions,

$$\theta_0 = \theta_0 - \alpha \frac{1}{m} \sum_{i=1}^m (s_{\theta}(X^i) - Y^i) \quad (10)$$

$$\theta_1 = \theta_1 - \alpha \frac{1}{m} \sum_{i=1}^m (s_{\theta}(X^i) - Y^i) X_1^{(i)} \quad (11)$$

$$\theta_2 = \theta_2 - \alpha \frac{1}{m} \sum_{i=1}^m (s_{\theta}(X^i) - Y^i) X_2^{(i)} \quad (12)$$

where the notation $:=$ represents that the set of the values of θ_j on the left side of the equation is equal to the set of the value on the right side, and α is the learning rate, which determines the efficiency of the gradient descent algorithm. If the learning rate is too small, a large number of steps will be needed to reach the global minimum. Conversely, if the learning rate is too large, the cost function will not converge. Thus, choose the right learning rate is crucial.

The learning rate can be calculate using

$$\alpha = \alpha_S * \alpha_D^{\frac{\text{global-step}}{\text{decay-step}}} \quad (13)$$

where α_S is the initial learning rate, α_D indicates the attenuation rate of each round of learning, global-step represents the current number of learning steps which is equivalent to how many times we have put batch into the learner, and decay-step is the number of steps per round of learning which is equal to the total number of samples divided by the size of each batch. Then the saturation of atmospheric light S_A is estimated. Owing to atmospheric light corresponds to the most dense haze area, so the 1/4 brightest region in the image is selected, and the minimum pixel value in the region is used as an estimate of S_A .

We implement the adaptive histogram equalization method [14] in the intensity channel. We obtain the transmission $t(x)$ based on the histogram theory. Then, the atmospheric light estimation method of He et al. is improved. In He et al.'s work [14], the top 0.1% of pixels in the dark

channel are taken as the atmospheric light. Although this method is robust, only one point is taken into account which maybe the reason that the A value of each channel is too high to result in color drift. Achieving satisfactory results with conventional methods is difficult when highlight areas exist in the image.

$$M(x) = \min_{c \in \{r, g, b\}}(I_c(x)) \quad (14)$$

Based on the work of He and others, we developed a method that can reduce the influence of highlight areas on the acquisition of atmospheric light. First, it's required a minimum channel map of the degraded remote sensing images. The minimum channel map can be calculated as follows:

$$Score_i = M_i - \delta 2_i, \quad i = 1, 2 \quad (15)$$

where i is the index of each region, $score_i$ is the score of region i , M_i represents the mean value of the region I and $\delta 2_i$ represents the variance in the region i . Then, the region with the highest score is taken as the candidate iterative region and is further divided into four smaller regions. The process continues until the size of the candidate region is smaller than the preset size threshold. The average of each channel in the last candidate region is selected as the result of A. Thus, we can obtain the haze-free intensity component image $I(x)$ because we have estimates of A and $t(x)$:

$$I(x) = \frac{I(x) - A}{t(x)} + A \quad (16)$$

Finally, these three channel images are transformed from HSI color space back to RGB color space.

III. EXPERIMENT

To validate the effectiveness of the method, we tested multiple remote sensing hazy images. The images used in this research were collected from the NASA Earth Observatory website and the Earth Explorer of the United States Geological Survey (USGS). The performance of the proposed method is compared with that of the Multi-scale Retinex method [12], the Tan's method [13] and the DCP method [14] are both qualitative and quantitative. Our method achieves a better result.

1. Quantitative results comparison

In order to quantitatively evaluate the algorithms, we select some classical evaluation indices, including the mean squared error (MSE), the structural similarity (SSIM), the

ratio of new visible edges (e), the gain of visibility level r^- and the fog aware density evaluator (FADE). Structural similarity (SSIM) is an objective evaluation index that is independent of the brightness and the contrast of the image and conforms to the characteristics of the human visual system. A high SSIM value indicates that the image with haze removed is very similar to the real image on the ground [19].

By comparing the processing results of each algorithm, we concluded that the SSIM value obtained by this method is higher; the results are shown in Table 1. The MSE can be utilized as a more convenient way to evaluate the degree of data variation [20, 21]. A high value of MSE indicates that the haze-removal algorithm is not effective while a low value of MSE indicates that the recovered image is valuable. The value of e evaluates the ability of the haze-removal method to recover the edges that are not visible in a hazy image. The value of r^- represents the average ratio of gradient specifications before and after dehazing [22]. The Fog Aware Density Evaluator [23] (FADE) is a contrast descriptor that indicates the visibility of a foggy scene by measuring the statistical regularity deviation of hazy images and haze-free images. A low value of the FADE implies better visibility enhancement. We show the corresponding MSE results produced by the different algorithms in Fig. 4, we list the values of SSIM, e , r^- and FADE.

To sum up, our method achieves the smallest values of MSE and FADE, the highest value of SSIM, e and r^- . Therefore, the results of these experimental data indicate that our algorithm achieves better performance in contrast enhancement, image structure information preservation, visible edge enhancement, and haze removal. As a consequence, the proposed method in this research is valuable for haze removal.

IV. CONCLUSION

We have developed a novel and effective de-hazing algorithm to achieve single remote-sensing image de-hazing. A Gamma correction model is proposed to estimate the saturation component. In addition, we used the adaptive histogram equalization method to the intensity component. Compared with the earlier haze removal methods, the experimental results demonstrate that the developed method can achieve better visual effect and better color restoration. Both qualitative evaluations and quantitative




Fig 3: (a) input image, from the input image obtained (b) hue image, (c) saturation image, (d) intensity image, (e) result of gamma correction applied on saturation image, (f) result of adaptive histogram equalization applied on intensity image, (g) enhanced intensity image, (h) output image.

assessments indicate that the proposed method achieves a better performance than the state-of-the-art methods with good visual effect and high quality. The following research will be aimed at dealing with dense haze.

REFERENCES

- [1] Cheng, F-C., C-H. Lin, and J-L. Lin. "Constant time O (1) image fog removal using lowest level channel." *Electronics Letters* 48.22 (2012): 1404-1406.
- [2] Im, Jaehyun, et al. "Dark channel prior-based spatially adaptive contrast enhancement for back lighting compensation." *Acoustics, Speech and Signal Processing (ICASSP), 2013 IEEE International Conference on. IEEE, 2013.*
- [3] Kang, Li-Wei, Chia-Wen Lin, and Yu-Hsiang Fu. "Automatic single-image-based rain streaks removal via image decomposition." *Image Processing, IEEE Transactions on* 21.4 (2012): 1742-1755.
- [4] Kil, Tae Ho, Sang H-wa Lee, and Nam Ik Cho. "A de-hazing algorithm using dark channel prior and contrast enhancement." *Acoustics, Speech and Signal Processing (ICASSP), 2013 IEEE International Conference on IEEE, 2013.*
- [5] Shuai, Yanjuan, Rui Liu, and Wenzhang He. "Image Haze Removal of Wiener Filtering Based on Dark Channel Prior." *Computational Intelligence and Security (CIS), 2012 Eighth International Conference on. IEEE, 2012.*
- [6] Tripathi, A. K., and S. Mukhopadhyay. "Single image fog removal using bilateral filter." *Signal Processing, Computing and Control (ISPC), 2012 IEEE International Conference on. IEEE, 2012.*
- [7] Wang, Yan, and Bo Wu. "Improved single image de-hazing using dark channel prior." *Intelligent Computing and Intelligent Systems (ICIS), 2010 IEEE International Conference on. Vol. 2. IEEE, 2010.*
- [8] Wei, Sun, and Han Long. "A New Fast Single-Image Defog Algorithm." *Intelligent System Design and Engineering Applications (ISDEA), 2013 Third International Conference on. IEEE, 2013.*
- [9] X-u, Haoran, et al. "Fast image de-hazing using improved dark channel prior." *Information Science and Technology (ICIST), 2012 International Conference on. IEEE, 2012.*
- [10] Yu, Jing, and Qingmin Liao. "Fast single image fog removal using edge-preserving smoothing." *Acoustics, Speech and Signal Processing (ICASSP), 2011 IEEE International Conference on. IEEE, 2011.*