

A Review Paper on Response Surface Method Analysis of Composite Material

Sarika Sharma¹, Prof. S.S.Kulkarni²

^{1,2}Dept of Mechanical Engineering

^{1,2}S. K. N.Sinhgad College Of Engineering Korti Pandharpur, India

Abstract- This papere valuates the Various optimization techniques have been proposed in metal cutting process for determining the optimum process design. Generally, the process design parameters in metal cutting processes are relatively few such as cutting speed, feed rate and depth of cut i.e. Independent parameters; however, their optimization remains a challenge due to several other factors related to processing conditions and shape complexities like Surface Roughness, MRR which are Dependent Parameters. In this project we introduced a new material through research which can decrease production development cost and time and also accelerate the process of product development.

Composite materials are light in weight and have a good strength which make the system reliable and robust. Composite material providing insight in system problem underlying physics and model weakness and also opening up new research fields and technologies which will create new growth opportunities. The proposed research work aims to investigate mechanical properties and machining parameter in turning of composite material. Optimum machining parameters are of great concern in manufacturing environments. The main objective of this research work is to optimize surface roughness of composite material specifically in turning process by changing parameter such as depth of cut, cutting speed and feed rate and also predict the mechanical properties of composite material.

The RSM optimization is needed in industry to increase the production rate by minimizing the surface roughness of the specimens.

I. INTRODUCTION

1.1GENERAL

Composite unite many of the best qualities that traditional materials have to offer. The two components of a composite include reinforcement and matrix. The matrix binds the reinforcement it together to merge the benefits of both original components. Composites are improving the design process and end products across industries. Each year composites continue to replace traditional materials like steel

and aluminium. As composite cost come down and design flexibility improves fibre reinforced composites like carbon fibre and fiberglass open up new design opportunities. Composites have a high strength to weight ratio. Composites are durable. Composites open up new design options. Composites are now easier to produce.

Machining of composite materials is difficult to carry out due to the anisotropic and non homogeneous structure of composites and to the higher abrasiveness of their reinforcing constituents. This is typically results in damage being introduced into the work piece and in very rapid wear development in the cutting tool. In metal cutting mechanism is plastic deformation. The material is softer than the tool and the cheap flows over the cutting edge. But in machining of composites the focus here will be CFRP there is no cheap to speak of. Instead the material removal mechanism might be better described as shattering. Rather than sharing material away, the impact of the cutting edge fractures the hard carbon fibres. In the process the cutting edge undergoes considerable abrasion that can lead to rapid wear. Carbide can work as a tool material do carbide tools machining composites often have to be changed frequently hence diamond tooling is likely to last much longer the choices in diamond tooling for CFRP include diamond grit plated onto a mandrel. Diamond coating applied through chemical vapour deposition or solid inserts made from polycrystalline diamond (PCD).The shattering of composites is like the deformation of metal in at least one way. Just as in metal cutting the energy of the cut it still transformed into heat. CFRP has a particularly hard time dissipating this heat. No chip is generated to carry the heat away and the material has low thermal conductivity. The resulting heat build of causes the danger of melting or otherwise damaging The matrix coolant might not help because coolant might not be allowed in the machining of certain composite parts. Therefore the tool and the tool path are all that remain to hold down the heat of machining. Sharp angles are generally one of the keys to accomplishing this. Sharp angle tools for composites feature high positive rake angles for a quick sharp clean cut that keeps heat to a minimum. Such tools also incorporate clearance angles that are sufficient to prevent the age of the tool from rubbing as it passes.

The purpose of optimization is to achieve the best design relative to a set of prioritized criteria or constraints. These include maximizing factors such as productivity, strength, reliability, efficiency and utilization. In any machining process apart from obtaining the accurate dimensions achieving a good surface quality and maximize and metal removal are also of utmost importance. A machining process involves many process parameters which directly or indirectly influence the surface roughness and metal removal rate of the product in common. Surface roughness and metal removal in turning process are varied due to various parameters of which feed, speed, depth of cut are important ones. The selection of proper combination of machining parameters yields the desired surface finish and metal removal rate the proper combination of machining parameters is an important task as it determines the optimal values of surface roughness and metal removal rate. It is necessary to develop mathematical models to predict at the influence of operating conditions. The preparation of quality surfaces is very important process in the surface engineering the surface roughness will influence the quality and effectiveness of the subsequent coatings for protection against corrosion and wear resistance and finishes quality of decorative layers.

1.2 Motivation and Objectives

Optimization is an act, process or methodology of obtaining the best results under given circumstances. The word 'Optimum' is taken as 'Minimum' or 'maximum' depending upon the circumstances. While designing, construction, and maintenance of any engineering system, engineers have to take many technological and managerial decisions at certain stages. The ultimate aim of all such decisions is either to minimize the effort required or to maximize the desired benefit. Since the effort required or the benefit desired in any practical situation can be defined as the process of finding the conditions that give the maximum or minimum value of a function. So in our case we have to minimize the surface roughness so that the specimen after turning process will be smooth.

Various optimization techniques have been proposed in metal cutting process for determining the optimum process design. Generally, the process design parameters in metal cutting processes are relatively few such as cutting speed, feed rate and depth of cut i.e. Independent parameters; however, their optimization remains a challenge due to several other factors related to processing conditions and shape complexities like Surface Roughness, MRR which are Dependent Parameters.

In this project we introduced a new material through research which can decrease production development cost and time and also accelerate the process of product development. Composite materials are light in weight and have a good strength which make the system reliable and robust. Composite material providing insight in system problem underlying physics and model weakness and also opening up new research fields and technologies which will create new growth opportunities.

The RSM optimization is needed in industry to increase the production rate by minimizing the surface roughness of the specimens.

1.3 AIM AND OBJECTIVES

AIM

Experiment Investigation of mechanical properties and machining parameter in turning of composite material using Response surface method

Objectives

1. To select & manufacture Composite material.
2. To investigate Mechanical Properties of Composite Material.
3. To predict machining parameters that contributes to optimize Surface Roughness.
4. To compare Mechanical properties & Surface roughness of composite with another material.

II. LITERATURE REVIEW

1.Vipin Kumar Sharma Qasim Murtaza S.K. Garg "RESPONSE SURFACE METHODOLOGY & TAGUCHI TECHNIQUES TO OPTIMIZATION OF C.N.C. TURNING PROCESS".[1]

This paper outlines the fractional factorial approach of D.O.E. techniques (Taguchi & Response Surface Methodology) are applied to optimize turning process parameter in order to obtain better surface finish. The turning parameters evaluated are cutting speed, feed, and depth of cut. An orthogonal array, signal-to-noise (S/N) ratio, and Pareto analysis of variance (ANOVA) are employed to analyze the turning parameters. Main and interaction effects of process parameters on the quality characteristics (surface roughness) have been analyzed and the results shows that feed and interaction of cutting speed depth affects the surface finish greatly. The parameter for getting better surface finish are

cutting speed of 2400 rpm, feed rate 40 mm/min, and depth of cut 0.5 mm.

2. Dr. M. K. Pradhan "Optimization of MRR, TWR and surface Roughness of EDMed D2 Steel using an integrated approach of RSM, GRA and Entropy measurement Method".[2]

In this research, a hybrid optimization approach is proposed for the determination of the optimal process parameters that maximizes the material removal rate, minimize surface roughness & the tool wear rate. Three input parameters namely pulse current (I_p), pulse duration (T_{on}) & pulse off time (T_{off}) of electrical discharge machining were considered for this analysis. The experiments were planned as per response surface methodology and subsequently grey relational analysis has been used to optimize the aforesaid response and finally the weight of the responses was determined by the entropy measurement method. Analysis of variance is used to find the effect of input parameters on the responses and found that T_{on} was the most influencing parameter followed by I_p and T_{off} in EDM of D2 steel. The R^2 value for the grey relational grade model was 0.919. These results provide useful information about how to control the responses and ensure higher productivity, high-accuracy and higher surfaces-quality surfaces. This method is simple with easy operability. The assessment outcome provides a scientific reference to obtain the minimal condition of surface integrity, and they were found to be a pulse current of 5A, pulse duration of 60 μ s, and pause time of 45 μ s.

3. Adrian, BEJINARU MIHOC Gheorghe "MANUFACTURING PROCESS AND APPLICATIONS OF COMPOSITE MATERIALS".[3]

This paper is presented some manufacturing processes of composites, as laminating, filament winding, pultrusion, resin transfer molding, and their large applications in aeronautics, automotive, maritime, etc. Also, a FEA of slide bearing form PA6 reinforced with glass fibers that change the slide bearing from bimetallic used of machine tools is analyzed.

4. Sivaraos, K.R. Milkey, A.R. Samsudin, A.K. Dubey, P. Kidd "Comparison between Taguchi Method and Response Surface Methodology (RSM) in Modelling CO2 Laser Machining".[4]

The applications of Taguchi method and RSM to modelling the laser parameters when machining industrial PVC foams is presented. The influence of cutting speed, laser power, frequency, duty cycle, and gas pressure on kerf width

has been considered in this investigation according to Taguchi method using a standard orthogonal array L27 and RSM using a central composite design. Taguchi technique as well as 3D surface plot of RSM revealed that the cutting speed is the most significant factor in minimizing kerf width followed by laser power and etc. A predictive mathematical model was then developed through a regression analysis in both analytical tools to study the response. Though both the techniques predicted near values of average error, the RSM technique seems to be more promising in predicting the response via mathematical modelling over the Taguchi technique.

5. Pranav R. Kshirsagar, Somesh R. Pise, Sunil A. Pokalekar, Mahindra Goudadaba, Duradundi Sawant. Badkar "Optimization of Surface Roughness of EN8 Steel in CNC Turning Operation by Taguchi Concept".[5]

In the present research work the effect of CNC machining parameters: cutting speed C_s , depth of cut D_c and feed rate F on the surface roughness (R_a) in a turning of EN8 Steel is investigated using the Taguchi method and ANOVA. A three level, three parameter design of experiment, L9 orthogonal array using Minitab 14 software, the signal-to-noise (S/N) ratio is employed to study the performance characteristics in the turning of EN8 Steel by taking coated carbide inserts cutting tool on CNC turning machine. The statistical methods of signal to noise ratio (S/N ratio) and the analysis of variance (ANOVA) are applied to investigate effects of cutting speed, depth of cut and feed rate on surface roughness. The analysis of variance (ANOVA) is applied to study the optimization of the process parameters affecting the surface roughness was achieved with the Taguchi orthogonal test design. The results are verified by taking confirmation experiments. The present investigation indicates that feed rate is the most significant factors influencing the surface roughness R_a for turning of EN8 steel material.

6. Ranganath M S, Vipin & Harshit "Optimization of Process Parameters in Turning Operation Using Response Surface Methodology: A Review".[6]

The parameters affecting the roughness of surfaces produced in the turning process for various materials have been studied by many researchers. Design of experiments were conducted for the analysis of the influence of the turning parameters such as cutting speed, feed rate and depth of cut on the surface roughness. The results of the machining experiments were used to characterize the main factors affecting surface roughness by the DOE techniques like Taguchi, Full factorial, Response Surface Methodology and other methods. The key element for achieving high quality at low cost is Design of Experiments (DOE). Response surface

methodology (RSM) is an effective tool for robust design, it offers a simple and systematic qualitative optimal design to a relatively low cost. In this paper RSM, an approach of DOE used by various researchers to analyze the effect of process parameters like cutting speed, feed, and depth of cut on Surface Roughness of work material while machining with various tools and to obtain an optimal setting of these parameters that may result in good surface finish have been discussed.

7. Rupinder Singh and J. S. Dureja "Comparing Taguchi Method and RSM for Optimizing Flank Wear and Surface Roughness During Hard Turning of AISI D3 Steel".[7]

The present work attempts to investigate tool wear (flank wear) and surface roughness (Ra) during finish hard turning of AISI D3 steel (58HRC) with coated carbide (TiSiN–TiAlN PVD coated) cutting tool. Taguchi L9 (3)3 orthogonal array has been applied for experimental design. Signal-to-noise (S/N) ratio (Lower the best) and analysis of variance (ANOVA) analyses were performed to identify significant parameters influencing tool wear and Ra. The cutting speed and feed were the most significant factor influencing tool wear (flank wear), and feed is the most significant factor influencing Ra. Mathematical models for both response parameters, i.e., tool wear and Ra were obtained through regression analysis. The confirmation experiments carried out at optimal combination of parameters given by Taguchi analysis predicted the response factors with less than 5 % error. In addition to this desirability function module, response surface methodology (RSM) was applied to arrive at the optimal setting of input parameters to minimize tool wear and Ra and to compare this with optimal setting of parameters given by Taguchi analysis. The optimization results provided by desirability function optimization is quite close to the optimal solutions provided by Taguchi analysis.

8. T. Sasimurugan and K. Palanikumar Analysis of the Machining Characteristics on Surface Roughness of a Hybrid Aluminium Metal Matrix Composite (Al6061-SiC-Al₂O₃)[8]

Aluminium Metal matrix composites are finding increased applications in many areas. Adding of the third element to the metal matrix make the composite hybrid. This paper presents The study on the surface roughness characteristics of a hybrid aluminium metal matrix composites. The experimental studies were carried out on a lathe. The characteristics that influence the surface roughness such as feed rate depth of cut and cutting speed where studied which made the analysis come to a conclusion that the surface roughness is increases with the increase of feed rate and it

reduces the surface roughness with the increase of cutting speed.

9. Gurpreet Singh , Maninder Pal Singh , Gurmeet Singh "Optimization of the machining parameters for surface roughness during turning of Al/SiC/Gr Hybrid MMC"[9]

In this paper the experimental investigation of turning of Al/SiC/GrMMC components was carried to optimise machining parameters to minimise surface roughness. The experiment is conducted based on taguchi method

10. STMahavuhungu, E T Akinlabi, M A Onitiri, FMVarachia, "Aluminium matrix composites for industrial use advances and trends"[10]

This paper presents The the industrial use of aluminium matrix composites its advances and trends. Aluminium metal matrix composites possess the the important feature such as superior strength to weight ratio good ductility high strength and high modulus low thermal expansion coefficient excellent wear resistance and excellent corrosion resistance high-temperature creeper resistance and better fatigue strength. they are widely used for high performance applications such as automotive industrial military aerospace and electricity industries.

Summary of Literature:

From above reviews it is clear that there is wide application of composite materials in industries. Those materials should have the low cost ,reduced production time with good quality of surface roughness . So the RSM optimization of machining parameters on turning of composite materials gives the optimal solution for multiple variables.

III. EXPECTED CONCLUSIONS

- Composite material is being used to carry out experimentation for determining the combination of process parameters that helps to achieve a better surface roughness. Based on the experimentation and analysis carried out the concluding observation will be recorded.
- The predicted surface roughness from response surface methodology was compared with the one obtained from experimentation.

Our expectation based on the correlation will be found out from the above analysis. It is suggested that response surface methodology can well be utilized for predicting the surface roughness of carbon fiber reinforced polymer composites.

REFERENCES

- [1] Vipin Kumar Sharma, Qasim Murtaza & S.K. Garg "RESPONSE SURFACE METHODOLOGY & TAGUCHI TECHNIQUES TO OPTIMIZATION OF C.N.C. TURNING PROCESS". International Journal of Production Technology and Management (IJPTM), ISSN 0976 – 6383(Print) ISSN 0976 – 6391(Online) Volume 1 Number 1, July - Aug (2010), pp. 13-31.
- [2] Dr. M. K. Pradhan "Optimization of MRR, TWR and surface Roughness of EDMed D2 Steel using an integrated approach of RSM, GRA and Entropy measurement Method". 978-1-4673-6150-7/13/\$31.00 ©2013 IEEE.
- [3] P. Adrian, BEJINARU MIHOC Gheorghe "MANUFACTURING PROCESS AND APPLICATIONS OF COMPOSITE MATERIALS". ANNALS of the ORADEA UNIVERSITY Fascicle of Management and Technological Engineering, Volume IX (XIX), 2010, NR2
- [4] Sivaraos, K.R. Milkey, A.R. Samsudin, A.K. Dubey, P. Kidd "Comparison between Taguchi Method and Response Surface Methodology (RSM) in Modelling CO2 Laser Machining". Volume 8 Number 1, February. 2014 ISSN 1995-6665.
- [5] Pranav R. Kshirsagar, Somesh R. Pise, Sunil A. Pokalekar, Mahindra Goudadaba, Duradundi Sawant. Badkar "Optimization of Surface Roughness of EN8 Steel in CNC Turning Operation by Taguchi Concept". 06 April 2016 ISSN 2348-7550.
- [6] Ranganath M S, Vipin & Harshit "Optimization of Process Parameters in Turning Operation Using Response Surface Methodology: A Review". ISSN 2250-2459, ISO 9001:2008 Certified Journal, Volume 4, Issue 10, October 2014
- [7] Rupinder Singh and J. S. Dureja "Comparing Taguchi Method and RSM for Optimizing Flank Wear and Surface Roughness During Hard Turning of AISI D3 Steel". DOI: 10.1007/978-81-322-1859-3_13.
- [8] T. Sasimurugan and K. Palanikumar "Analysis of the Machining Characteristics on Surface Roughness of a Hybrid Aluminium Metal Matrix Composite (Al6061-SiC-Al2O3)" Article in Journal of Minerals and Materials Characterization and Engineering · January 2011 Vol. 10, No. 13, pp. 1213-1224
- [9] Gurpreet Singh, Maninder Pal Singh, Gurmeet Singh "Optimization of the machining parameters for surface roughness during turning of Al/SiC/Gr Hybrid MMC" International Journal of Engineering Research & Technology (IJERT) Vol. 2 Issue 11, November - 2013 ISSN: 2278-0181
- [10] ST Mahavuhungu, E T Akinlabi, M A Onitiri, FM Varachia, "Aluminium matrix composites for industrial use advances and trends" SMPM2017, 23-25 January 2017 Procedia Manufacturing 7 (2017) 178 – 182