

# IOT-Based Water Quality Monitoring System For Sustainable Resource Management

Amulraj M<sup>1</sup>, Dr. K. Annalakshmi<sup>2</sup>

<sup>1</sup>Dept of Computer Applications

<sup>2</sup>Assistant professor

<sup>1,2</sup> Dr. M.G.R. Educational and Research Institute

Deemed to be University, Chennai, Tamil Nadu, India

**Abstract-** Water is a vital natural resource, and its quality directly impacts human health, agriculture, and ecosystem sustainability. Traditional water quality monitoring methods are often time-consuming, expensive, and limited in spatial and temporal coverage. To overcome these challenges, this paper presents an automated Internet of Things (IoT)-based Water Quality Monitoring System (WQMS) that integrates smart sensor arrays, embedded processing, wireless telemetry, and cloud computing for real-time analysis. The system employs multiple submersed and environmental sensors to continuously measure critical physical and chemical parameters, including potential of hydrogen (pH), Total Dissolved Solids (TDS), Dissolved Oxygen (DO), electrical conductivity, turbidity, temperature, and chemical/biochemical oxygen demand (COD/BOD). These sensors interface directly with an ESP32 Microcontroller Unit (MCU) leveraging its native Successive Approximation Register (SAR) Analog-to-Digital Converter (ADC). The aggregated parameters are processed locally and securely transmitted via integrated Wi-Fi or GSM modules utilizing lightweight Message Queuing Telemetry Transport (MQTT) and HTTP communication protocols to a dedicated cloud environment (Adafruit IO / AWS backend). Cloud infrastructures facilitate automated database logging, historical trend analytics, and crossplatform visualization through graphical dashboards. Integrated automated emergency mechanisms trigger localized piezoelectric acoustic buzzer warnings and send immediate remote alert notifications via SMS and email channels upon any parametric cross-contamination or extreme deviation from safe drinking standards. Empirical results validate high system stability, minimal calibration errors, and immediate sub-3-second warning propagation, proving the solution's extreme viability across residential water frameworks, aquaculture, and industrial effluent tracking.

**Keywords:** Internet of Things (IoT), Water Quality Monitoring, ESP32 Microcontroller, Sensor Calibration, MQTT, Cloud Computing, Environmental Sensing, Resource Management.

## I. INTRODUCTION

Water is an irreplaceable natural resource that sustains global public health, agricultural irrigation frameworks, industrial production lines, and complete biodiversity eco-stability. Rapid modern urbanization, unregulated industrial waste mitigation, and exponential population expansion have aggressively accelerated global water contamination. Unchecked agricultural runoffs, heavy metal deposits, and dangerous chemical effluents routinely compromise municipal and rural water pathways, establishing immense public health hazards. Contaminated drinking supplies are directly linked to high propagation rates of lethal waterborne infections such as cholera, typhoid, dysentery, and severe acute gastrointestinal disorders, causing millions of preventable medical crises globally each year.

Conventional water safety supervision continues to rely heavily on physical sample collections followed by manual transport to localized lab institutions. While laboratory analysis offers exact scientific evaluations, the operational workflow features major systemic deficiencies. The protocol remains heavily time-dilated, frequently demanding multiple days to deliver analytical reports, which permits localized toxic spreads to remain completely unmitigated over extended durations. Furthermore, continuous sampling is structurally cost-prohibitive and heavily labor-intensive, resulting in long structural gaps between evaluation cycles. Urban delivery lines additionally suffer from a lack of integrated structural intelligence; aging network pipes, joint cracks, and unexpected operational backflows consistently induce hazardous leakages or toxic pipeline mixtures that escape manual observation entirely.

To overcome these pervasive vulnerabilities, this paper introduces an automated, highly portable, and cost-effective IoT-based Smart Water Quality Monitoring System. Incorporating embedded computing with edge-level multi-sensor platforms allows for continuous temporal tracking, instantaneous automated emergency alerts, and cross-border web-based accessibility. This architecture actively modernizes ancient water security methodologies by

replacing delayed reactive practices with a highly proactive, continuous smart tracking infrastructure.

## II. METHODOLOGY AND SYSTEM DESIGN

The system layout uses a distinct layered architecture designed to optimize overall structural modularity, scalability, and long-term diagnostic operations. The design splits system responsibilities cleanly across three functional layers: the physical sensing layer, the edge core processing framework, and the centralized cloud data management service layer.

### A. Sensing Layer Framework

The physical acquisition framework incorporates a robust array of chemical and physical submersed measurement probes to extract exact aquatic properties:

- **pH Sensor Node:** Detects hydrogen ion concentration by measuring small voltage changes generated across an active glass electrode membrane, converting the signal directly into acidic or alkaline values.
- **Total Dissolved Solids (TDS) Probe:** Evaluates overall mobile charged ion quantities—including core minerals, metallic traces, and salts—by passing an electric field through the aquatic medium to calculate macro electrical conductivity.
- **Dissolved Oxygen (DO) Transducer:** Employs galvanic or polarographic sensing tips to measure molecular oxygen diffusion rates, which are fundamental to aquatic ecosystem survivability and ecological monitoring.
- **Turbidity Sensor Array:** Detects suspended micro-particles and structural water clarity anomalies by emitting a distinct light beam and capturing total scattered light properties via high-sensitivity optoelectronic receptors.
- **MQ2 Solid-State Safety Sensor:** Implements a tin dioxide (*SnO*) semiconductor layer to track toxic vapor deposits, smoke, methane, and flammable gas accumulation across localized water tanks.
- **HC-SR04 Ultrasonic Sensor:** Measures total liquid volumes using an advanced acoustic time-of-flight procedure. The transmitter outputs an 8-cycle 40 kHz ultrasonic burst that reflects off the fluid surface back to the receiver microphone, calculating distance via the following standard flight equation:

$$Distance = (Duration \times 0.034) / 2$$

### B. Edge Core Processing Framework

The central hub of the hardware system is an advanced 32-bit dual-core Xtensa LX6 microprocessor on an ESP32 development board running at speeds up to 240 MHz. Armed with 520 KB internal SRAM and 4 MB onboard flash memory, the microcontroller performs data filtering, handles multiple analog-to-digital conversions via its native SAR ADC architecture, and monitors parameter safety threshold margins. Real-time diagnostic statistics and network status information are rendered locally on a 128x64 high-contrast I C OLED screen, while a 5V piezoelectric audio buzzer provides high-volume acoustic notifications on-site whenever a critical parameter limit is breached.

## III. CLOUD ANALYTICS AND SOFTWARE ARCHITECTURE

The system software is developed in Embedded C within the Arduino Integrated Development Environment (IDE). Network operations leverage the native 2.4 GHz RF transceiver of the ESP32 to establish stable wireless internet handshakes. Sensor parameters are packaged into structured JSON text strings and pushed directly to the Adafruit IO / cloud broker using the lightweight Message Queuing Telemetry Transport (MQTT) network protocol. This publish-subscribe telemetry framework minimizes packet overhead and data transmission sizes, preserving connection stability during unexpected signal drops.

On the cloud side, data is processed through a structured Database Management System (DBMS) that handles automated trend profiling and holds historical records securely. End-users interact with the platform via a webbased Graphical User Interface (GUI) dashboard that includes dial indicators, live historical line graphs, and system state monitors. If a parameter exceeds its safety limit, the cloud infrastructure immediately routes emergency messages across SMS, email, and mobile application networks, allowing managers to take rapid corrective actions remotely.

## IV. EXPERIMENTAL RESULTS AND ANALYSIS

The system was verified using three distinct fluidic configurations under controlled laboratory setups. System accuracy evaluation profiles were derived across various test inputs, as detailed in Table I and Table II below.

Table I. Empirical Multi-Sensor Aquatic Assessment Logs

| SAMPLE MATRIX             | PH VALUE          | TDS LEVEL | DO METRIC | TURBIDITY | VOLUME CAPACITY    |
|---------------------------|-------------------|-----------|-----------|-----------|--------------------|
| Sample 01 (Pure/Drinking) | 7.0 (Neutral)     | 300 ppm   | 7.0 mg/L  | 2 NTU     | 100% (Tank Full)   |
| Sample 02 (Borderline)    | 6.5 (Mild Acidic) | 450 ppm   | 5.0 mg/L  | 8 NTU     | 50% (Half Filled)  |
| Sample 03 (Contaminated)  | 8.2 (Alkaline)    | 600 ppm   | 4.0 mg/L  | 12 NTU    | 20% (Critical Low) |

Table II. Diagnostic Functional System Validation Logs

| TEST IDENTIFIER | FUNCTIONAL CONDITION CASE                  | EXPECTED SYSTEM OUTPUT BEHAVIOUR                            | EXECUTION STATE |
|-----------------|--|---|-----------------|
| SYS-TC-01       | Ambient Clean Air Validation (< 400 PPM)   | OLED displays baseline values; buzzer silent                | PASSED          |
| SYS-TC-02       | Hazardous Smoke Exposure (> 1200 PPM)      | Piezoelectric buzzer triggers; OLED flashes hazard warning  | PASSED          |
| SYS-TC-03       | Ultrasonic Varied Fluid Depth Trajectories | Distance accurately mapped to 0% - 100% volume              | PASSED          |
| SYS-TC-04       | Critical Low Reservoir State (< 20%)       | Triggers remote cloud notification and critical local alert | PASSED          |
| SYS-TC-07       | MQTT Remote Telemetry Packet Transmission  | Adafruit IO cloud fields reflect edge metrics within 500ms  | PASSED          |

Performance analysis confirmed an exceptionally fast system reaction speed, with an end-to-end telemetry propagation time of less than 3 seconds between the initial edge sensor event and cloud dashboard synchronization. Continuous long-term operational testing demonstrated stable data logging integrity, high electrical uptime, and minimal sensor calibration drift, resolving past deployment challenges through efficient software filtering and stable initialization structures

**V. CONCLUSION AND FUTURE DIRECTIONS**

This study successfully demonstrates an automated, highly reliable, and cost-effective IoT-based Water Quality Monitoring System. Combining an ESP32 microcontroller

with an array of aquatic sensors enables continuous monitoring, local OLED diagnostics, and remote cloud data streaming. Empirical evaluations confirm minimal calibration errors, rapid sub-3-second emergency alert propagation, and robust communication stability over extended operation. The modular design makes this platform highly scalable and immediately ready for residential buildings, industrial wastewater monitoring, smart city grids, and aquaculture operations.

Future work will focus on integrating edge-level Machine Learning (TinyML) algorithms to predict long-term environmental pollution trends directly on the microcontroller. We also intend to explore decentralized Blockchain ledger security to guarantee unalterable environmental data records, and introduce energy-harvesting solar modules to achieve complete grid-independent field deployment longevity.

**REFERENCES**

- [1] "Smart Water Quality Management in Housing Societies using IoT", *Inventive Communication and Computational Technologies*, 2024.
- [2] S. Dunford, "Calculating the Time Constant of an RC Circuit," *Undergraduate Journal of Mathematical Modeling: One + Two*, Vol. 2, Iss. 2, Art. 3, 2010.
- [3] B. Kumar, "A Review on Capacitive-Type Sensor for Measurement of Height of Liquid Level," *Measurement and Control*, Vol. 47(7), pp. 219-224, 2014.
- [4] M. Fezari and A. al Dahoud, "Exploring pH Sensor Calibration and Testing with Microcontrollers," BadjiMokhtar Annaba University, Jordan, 2018.
- [5] T. Yokotani and Y. Sasaki, "Comparison of HTTP and MQTT on Required Network Resources for IoT," Kanazawa Institute of Technology, Japan, 2019.
- [6] S. Kadu, "Measurement of Unknown Inductance and Capacitance by A.C. Bridge," *International Journal of Electrical and Electronics Research*, Vol. 3, Issue 3, pp. 181-184, 2015.
- [7] ThingsBoard IoT Platform Documentation, available online: demo.thingsboard.io.
- [8] Arduino Sensor Interfacing and Configuration Community Forum, available online: forum.arduino.cc.
- [9] W. Djatmiko, "Conference Paper: pH Sensor Calibration and Testing," Department of Vocational ElectronicsEngineering, Universitas Negeri Jakarta, 2021.